



75L PUMP AWAY MOBILE OIL DRAINER

MODEL NO: AK450DX

Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.

IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.



Refer to instruction manual



Wear eye protection



Wear protective gloves

1. SAFETY

- WARNING!** Ensure Health & Safety, local authority, and general workshop practice regulations are adhered to when using this equipment.
 - WARNING! DO NOT** pollute the environment by allowing uncontrolled discharge of waste oil. Replace damaged parts. Use genuine parts only. Non authorised parts may be dangerous and will invalidate the warranty.
 - ✓ Keep the drainer clean and in good condition for best and safest performance.
 - ✓ Wear appropriate protective clothing.
 - ✓ Use drainer in an appropriate working area for its function. Keep area clean and tidy and free from unrelated materials and ensure there is adequate lighting.
 - ✓ Ensure the floor is not slippery and wear non slip shoes.
 - ✓ Keep children and unauthorised persons away from the working area.
 - ✓ Dispose of waste liquids in accordance with local authority regulations.
 - WARNING! DO NOT** allow uncontrolled discharge of fluids thus polluting the environment.
 - * **DO NOT** position drainer in such a way that it will cause potential hazards when moving, holding for draining or storing.
- IMPORTANT:** AK450DX must be used in conjunction with a wall mounted air pump, model no: AK450DP in order to discharge waste oil (not supplied with this unit).

2. INTRODUCTION

75L Reservoir and telescopic funnel fitted with grid filter. Fitted with female dry-fit coupling for connection to Model No. AK450DP Pump-Away Station. Includes full drum indicator.

3. SPECIFICATION

Model No	AK450DX
Capacity	75L
Collection bowl capacity	18L
Gravity discharge	no
Gravity feed	yes
Max. height to pan	1620mm
Min. height to pan	890mm
Oil discharge pressure (bar).....	0.5bar
Pump discharge	no
Temperature range.....	<55°C



4. ASSEMBLY

- 4.1. Unscrew the complete axle assembly from the transportation position. Use the nuts, bolts, and washers that are provided to fit the axle assembly and position the castor wheels as illustrated in the parts diagram.
- 4.2. Screw the drainage tube (item 3) into the collection bowl (item 2).
- 4.3. Introduce the drainage tube through the height adjustment adaptor into the reservoir and tighten the scalloped hand wheel (item 4).
- 4.4. Place the filter into the collection bowl (item 2).

5. OPERATION

- 5.1. **COLLECTION OF WASTE OIL**
 - 5.1.1. If unit has been used to drain a previous vehicle, check the oil level indicator float to ensure there is sufficient remaining capacity left before you use the unit.
 - 5.1.2. Place the unit under the raised vehicle and adjust the collection bowl to the desired height and tighten the scalloped hand wheel of the adjustable height adaptor.
- 5.2. **EVACUATION OF WASTE OIL FROM UNIT**
 - WARNING!** Ensure all waste is disposed of in accordance with local regulations.
 - 5.2.1. Take the discharge hose of wall mounted pump unit AK450DP and connect the female coupling to the male coupling of the pan unit and evacuate waste accordingly.

6. MAINTENANCE

- 6.1. Keep the collection bowl and unit clean and ensure there are no blockages in the evacuation outlets.
- 6.2. Oil wheels if necessary
- 6.3. When not in use store the unit in a safe, dry, childproof area.



ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.

Note: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

Important: No Liability is accepted for incorrect use of this product.

Warranty: Guarantee is 12 months from purchase date, proof of which is required for any claim.

Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk. IP32 7AR



01284 757500



01284 703534



sales@sealey.co.uk



www.sealey.co.uk