

Thank you for purchasing a Sealey product. Manufactured to a high standard this product will, if used according to these instructions and properly maintained, give you years of trouble free performance.



IMPORTANT

PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS AND CAUTIONS. USE THIS PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE, OR PERSONAL INJURY, AND WILL INVALIDATE THE WARRANTY. RETAIN THESE INSTRUCTIONS FOR FUTURE USE.

1. SAFETY INSTRUCTIONS

- ✓ Replace damaged parts. *Use recommended parts only. Non authorised parts may be dangerous and will invalidate the warranty.*
 - ✓ Keep the drainer clean and in good condition for best and safest performance.
 - ✓ Wear appropriate protective clothing.
 - ✓ Use drainer in an appropriate working area for its function. Keep area clean and tidy and free from unrelated materials and ensure there is adequate lighting.
 - ✓ Ensure the floor is not slippery and wear non slip shoes.
 - ✓ Keep children and unauthorised persons away from the working area.
 - ✓ Dispose of waste liquids in accordance with local authority regulations.
 - ☐ **WARNING!** DO NOT allow uncontrolled discharge of fluids thus polluting the environment.
 - ✗ DO NOT position the drainer in such a way that it will cause potential hazards when moving, holding for draining or storing.
- ▲ **IMPORTANT:** AK464DX must be used in conjunction with a wall mounted air pump, model no: AK450DP in order to discharge waste oil (not supplied with this unit).

2. DESCRIPTION

Description.

These steel drain pans are designed to collect waste oil via the pan's top collection facility. The pans have front wheel steering and are suitable for use on forecourts as well as workshop floors. The 95 litre capacity is ideal for use with commercial vehicles. Model AK465D is fitted with a gravity drain tap and model AK464DX has a dry-fit male coupling for connection to wall mounted air pump AK450DP.

3. SPECIFICATIONS & PARTS

AK465D & AK464DX
 Maximum capacity . . . 95litres
 Height255mm Inc handle
 Length690mm
 Width108mm
 Net weight29kg

AK465D Discharge . . .Gravity
 AK464DX Discharge . .Air pump

Drainer pan parts:
 Reservoir with handle
 4 castor wheel assemblies.
 Perforated filter plate
 (for centre of unit).
 AK465D Gravity drain tap..... Part No 179/19751.
 AK464DX Dry fit coupling.....Part No 179/19774.



4. OPERATING INSTRUCTIONS

- 4.1. Collection of waste oil**
- 4.1.1. If unit has been used to drain a previous vehicle check to ensure there is sufficient remaining capacity left before you next use pan.
 - 4.1.2. Place the pan under the vehicles sump and drain accordingly.
 - 4.1.3. When completed remove pan and wipe up any spillage.
- 4.2. Evacuation of waste oil from pan unit. ☐ WARNING! ensure all waste is disposed of in accordance with local regulations.**
- 4.2.1. AK465D connect a suitable discharge hose, or position the gravity drain tap over a suitable outlet and open the tap.
 - 4.2.2. AK464DX take the discharge hose of wall mounted pump unit AK450DP and connect the female coupling to the male coupling of the pan unit and evacuate waste accordingly.
- When not in use store pans in a safe, dry, childproof location.

NOTE: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.
IMPORTANT: No liability is accepted for incorrect use of product. **WARRANTY:** Guarantee is 12 months from purchase date, proof of which will be required for any claim. **INFORMATION:** Call us for a copy of our latest catalogue on 01284 757525 and leave your full name and address including your postcode.