



# TIG WELDING GAUNTLETS - PAIR

MODEL NO: **SSP142.V4**



Thank you for purchasing a Sealey product. Manufactured to a high standard, this product will, if used according to these instructions, and properly maintained, give you years of trouble free performance.



### REFER TO INSTRUCTIONS

**IMPORTANT:** PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS & CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. KEEP THESE INSTRUCTIONS SAFE FOR FUTURE USE.

## 1. INTRODUCTION

Quality goat skin TIG welding leather gauntlets with 160mm split cow leather cuff. 330mm Length. Conforms to BS EN 388 and BS EN 12477:2001. Size range: 9,10, 11.

**Notified Body:** ITS Testing Services (UK) Limited, Ventre Court, Meridian Business Park, Leicester, LE19 1WD

**Type Examination Certificate Number:** LEC FI00339435

**Approved Body No:** 0362

## 2. SAFETY

- ✓ For multilayer gloves that can be separated, the performance of levels are only applicable to the whole glove including all layers.
- ✗ **DO NOT** use where there is risk of entanglement by moving parts.
- ✓ When gloves are intended for arc welding: these gloves do not provide protection against electric shock caused by defective or live working equipment. Note that electrical resistance is reduced if the gloves are wet, dirty or soaked with sweat. This could increase the risk of electric shock.
- ✓ Protection is only given to the palm of the hand, the cuff will give adequate protection against small splashes of molten metal.
- ✓ There are substances in the glove which are known to cause allergies. A list of raw substances is available upon request.
- ✓ Type B gloves are recommend when high dexterity is required, as for TIG welding. Type A gloves are recommended for other welding processes.
- ✓ There is no standardized test method at present for detecting UV penetration of materials for gloves, but the current methods of construction of protective gloves for welders do not normally allow penetration of UV radiation.

## 3. PERFORMANCE

<b>Mechanical Risks</b> EN 388  2111X	Abrasion Resistance	1	(on 4 maxi)	The numbers indicate the performance level of the gloves. 1 = lowest 4 = highest 5 = highest for blade cut resistance  'X' indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.
	Blade Cut Resistance	1	(on 5 maxi)	
	Tear Resistance	1	(on 4 maxi)	
	Puncture Resistance	1	(on 4 maxi)	
	Cut Resistance Method (EN ISO 13997)	X	(A to F)	
<b>Thermal Risks (Heat/Flame)</b> EN 407  412X4X	Limited Flame Spread	4		
	Contact Heat	1		
	Convective Heat	2		
	Radiant Heat	X		
	Small drops of molten metal	4		
	Large drops of molten metal (if applicable)	X		
<b>Protective Gloves for Welders</b> EN 12477 	Burning Behaviour	B		Suitable for high dexterity tasks.
	Contact Heat	B		
	Small splashes of molten metal	B		

## 4. INSTRUCTIONS FOR USE

- 4.1. Place glove over hand fitting the thumb and fingers in the appropriate positions, making sure the glove is fitted comfortably to carry out the task at hand.
- 4.2. Remove by pulling the glove upward from the fingers.

## 5. MAINTENANCE

- ✗ **DO NOT** wash or tumble dry.
- ✓ The packaging provided with the glove is suitable for the required transport.
- ✓ This product does not have an expiry date, but should be replaced when worn/damaged.

This document has been drawn up according to Regulation (EU) 2016/425 as amended to apply to GB for Personal Protective Equipment. The declaration of conformity can be accessed at [www.sealey.co.uk](http://www.sealey.co.uk).



#### ENVIRONMENT PROTECTION

Recycle unwanted materials instead of disposing of them as waste. All tools, accessories and packaging should be sorted, taken to a recycling centre and disposed of in a manner which is compatible with the environment. When the product becomes completely unserviceable and requires disposal, drain any fluids (if applicable) into approved containers and dispose of the product and fluids according to local regulations.



REGISTER YOUR PURCHASE HERE

**Note:** It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice. Please note that other versions of this product are available. If you require documentation for alternative versions, please email or call our technical team on [technical@sealey.co.uk](mailto:technical@sealey.co.uk) or 01284 757505.

**Important:** No Liability is accepted for incorrect use of this product.

**Warranty:** Guarantee is 12 months from purchase date, proof of which is required for any claim.

EU | Sealey EU Ltd, Farney Street, Carrickmacross, Co. Monaghan, A81 PK68 Ireland

UK | Sealey Group, Kempson Way, Suffolk Business Park, Bury St Edmunds, Suffolk. IP32 7AR



01284 757500



[sales@sealey.co.uk](mailto:sales@sealey.co.uk)



[www.sealey.co.uk](http://www.sealey.co.uk)