

INSTRUCTIONS FOR:

LIFT ACTION PUMP FOR AdBlue

MODEL No: TP6806

Thank you for purchasing a Sealey product. Manufactured to a high standard this product will give you years of trouble free performance if these instructions are carefully followed and the product is correctly maintained.



IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS AND CAUTIONS. USE THIS PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WITHOUT ITS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE OR PERSONAL INJURY, AND WILL INVALIDATE THE WARRANTY. PLEASE RETAIN THESE INSTRUCTIONS FOR FUTURE USE.

1. SAFETY INSTRUCTIONS

- p WARNING! Ensure health & safety, local authority, and general workshop practice regulations are strictly adhered to when using this equipment.
- 3 Familiarise yourself with product application and limitations, as well as the specific potential hazards peculiar to this product.
- 3 Maintain the pump in good condition (use an authorised service agent).
- 3 Replace or repair damaged parts. Use genuine parts only. Non authorised parts will invalidate the warranty.
- 3 Pump is specifically designed to pump AdBlue (diesel engine fuel additive). May be used to pump other NON-Corrosive fluids such anti-freeze, degreasants, agricultural and industrial chemicals, and the like.
- 3 Ensure safety eye protection and protective clothing are worn when using this product.
- 3 Keep the work area clean, uncluttered and ensure there is adequate lighting.
- 3 Maintain correct balance and footing. Ensure the floor is not
- 3 Keep children and unauthorised persons away from the working area.
- 3 Dispose of waste liquids in accordance with local authority regulations.
- 7 DO NOT use to extract corrosive fluids.
- 7 DO NOT dismantle, tamper with or adapt the pump for any purpose other than for which it is designed.
- 7 DO NOT use the unit if it has been dropped or mishandled, check the unit to ensure there is no damage.
- 7 DO NOT use the pump as a handle to move the fluid drum.
- 3 Keep the pump clean and store in a safe dry, childproof location.
- p WARNING! DO NOT allow uncontrolled discharge of fluids thus polluting the environment.

2. APPLICATION

Heavy-duty polypropylene construction lift pump. Manufactured with polyethylene parts suitable for transferring AdBlue. Fitted with 2"BSP adaptor for use with 205ltr drums. Supplied with 1.36mtr discharge hose. Delivers approximately 250ml per stroke discharge.

(4) Pump required amount of fuel additive (3)Insert discharge pipe into measuring container (2) Loosen thumbscrew 'A' and screw adaptor into container opening, Tighten thumbscrew. (1) Insert pump into AdBlue container.

NOTE: It is our policy to continually improve products and as such we reserve the right to alter data, specifications and component parts without prior notice.

IMPORTANT: No liability is accepted for incorrect use of this product.

WARRANTY: Guarantee is 12 months from purchase date, proof of which will be required for any claim.

INFORMATION: For a copy of our latest catalogue and promotions call us on 01284 757525 and leave your full name and address, including postcode.



Sole UK Distributor, Sealey Group, Kempson Way, Suffolk Business Park, Bury St. Edmunds, Suffolk, IP32 7AR



