

Section 1. Product and Company Identification.

1.1 Model Number; 2100TB v2

1.2 Description; Viking Low Profile Professional Long Reach Trolley Jack with Rocket Lift 2 Tonne

Hydraulic Oil.

1.3 Manufacturer;

Jack Sealey Ltd.

t/a Sealey Group.

Kempson Way,

Bury St. Edmunds,

Suffolk,

IP32 7AR

UK

Jack Sealey (EU) Ltd

t/a Sealey Group.

Carrickmacross,

Carrickmacross,

Co. Monaghan,

A81 PK68

Ireland

technicalcompliance@sealey.co.uk

1.4 Emergency telephone number; 44 (0) 1284 757 500 (Office Hours)

Date of source compilation; 24/11/2025

Section 2. Hazards Identification.

Not relevant to the Model Number identified in 1.1 with Description stated in 1.2.

Section 3. Substances.

			Classification	
3.1 Chemical Name (substance)	3.1 CAS No.	3.2 Concentration Volume	Hazard Class & Category Code	Hazard Statements ¹
Base oil	8002-05-9	>95%	Carc 1B	H350
Di-tert-butylphenol	128-39-2	<5%	Skin Irrit. 2	H315
			Aquatic Acute 1	H400
			Aquatic Chronic 1	H410

¹For full text of Statements, see Section 16.



Section 4. First Aid Measures.

4.1 Description of first aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Skin Contact

Remove and wash contaminated clothing and shoes.

Wash exposed portions of the skin with soap and water.

Eye Contact

Flush eyes with large amounts of water for 15 minutes while holding eyelids open. Seek medical attention.

Ingestion

Seek medical attention.

Do not induce vomiting.

Section 5. Fire Fighting Measures.

5.1. Extinguishing media

Foam, dry powder, carbon dioxide. Do not use water jet.

5.2. Special hazards arising from the substance or mixture

The product can form flammable mixtures or can burn only on heating above the flash point.

5.3. Advice for fire-fighters

Do not enter confined fire space without protective equipment.

Only use water only to cool fire exposed containers. Do not use water to fight fire.

2100TB v2



Section 6. Accidental Release Measures.

6.1. Personal precautions, protective equipment and emergency procedures If handling hydraulic oil: Ensure there is adequate ventilation. Use Personal Protective Equipment, see Section 8.

6.2. Environmental precautions

Do not empty into drains. Take up with absorbent material, e.g. sawdust, sand or vermiculite. Place materials taken up into disposable container.

6.3. Methods and material for containment and cleaning up

Soak up residue with absorbent such as sawdust, sand or vermiculite. Dispose of absorbent and contaminated soil in the same manner as the product.

6.4. Reference to other sections

See Section 7 for information on Safe Handling See Section 8 for information of Personal Protective Equipment. See Section 13 for information on disposal.

Section 7. Handling and Storage.

7.1. Precautions for safe handling Avoid contact with eyes and skin. Ensure good ventilation in working area.

Keep away from heat and direct sunlight.

Keep receptacles tightly closed.

7.2. Conditions for safe storage, including any incompatibilities

Store in dry place at room temperature.

Store only in original container.

Store way from foodstuffs.

Store away from oxidising agents.

Keep away from ignition sources.

7.3. Specific end use(s)

Intended for use as hydraulic oil for the Model Numbers identified in 1.1 with Description stated in 1.2.

2100TB v2



Section 8. Exposure Controls/Personal Protection.

Eye/Face Protection

Wear chemical goggles to prevent eye contact.

Skin Protection

Use chemical-resistant gloves, if needed.

Respiratory Protection

Not required under normal usage. If product is handled in such a way as to create a vapour or mist, an approved respirator should be used to prevent overexposure.



Section 9. Physical and Chemical Properties.

9.1. Information on basic physical and chemical properties

The following information is not a technical specification or sales specification.

(a) Appearance: Pale yellow and transparent liquid.

b) Odour:

(c) Odour threshold;

No data available.

No data available.

No data available.

(e) Freezing point; -30°C.

(f) Initial boiling point and boiling range; No data available.

(g) Flash point; 163°C.

(h) Evaporation rate; No data available. (i) Flammability (solid, gas); No data available. (j) Upper/lower flammability or explosive limits; No data available. (k) Vapour pressure; No data available. (I) Vapour density; No data available. (m) Relative density; No data available. (n) Solubility(ies); Insoluble in water. (o) Partition coefficient: n-octanol/water; No data available. No data available. (p) Auto-ignition temperature; No data available. (q) Decomposition temperature; (r) Viscosity; No data available. (s) Explosive properties; No data available. (t) Oxidising properties. No data available.

9.2 Other information

No data available.



Section 10. Stability and Reactivity.

10.1. Reactivity No data available.

10.2. Chemical stability Stable at normal temperatures and pressure.

10.3. Possibility of hazardous reactions Hazardous polymerisation will not occur.

Avoid heat, flames, spark and other sources of ignition.

Avoid contact with incompatible material.

Strong oxidizing agents.

Oxides of carbon and various hydrocarbons formed when

burned.

Section 11. Toxicological Information.

11.1. Information on toxicological effects

10.6. Hazardous decomposition products

10.4. Conditions to avoid

10.5. Incompatible materials

Ingestion

Ingestion may be fatal or may produce serious damage to the health of the individual. Swallowing of the liquid may cause aspiration of vomit into the lungs with the risk of haemorrhaging pulmonary oedema progressing to chemical pneumonitis. Serious consequences may result. Signs and symptoms of chemical (aspiration) pneumonitis may include: coughing, gasping, choking, burning of the mouth, difficult breathing and bluish coloured skin (cyanosis)

Eyes

Material produces severe ocular lesions which can present twenty four hours or more after contact.

Skin

The material produces moderate skin irritation.

Inflammation present twenty for hours or more after the end of the exposure period.

Irritation may also be present after prolonged or repeated exposure, this may result in contact dermatitis (nonallergic). Dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (visiculation) scaling and thickening of the epidermis.

Do not expose open cuts, abraded or irritated skin to this material.

Entry into the blood-stream through cuts, abrasions, puncture wounds or lesions may produce systemic injury with harmful effects. Ensure that skin is suitably protected

Material on the skin evaporates rapidly and may cause tingling, chilling and even temporary numbness.

Inhalation

Ensure adequate ventilation to keep exposure at minimum



Section 12. Ecological Information.

12.1. Toxicity	No data available.
12.2. Persistence and degradability	No data available.
12.3. Bioaccumulative potential	No data available.
12.4. Mobility in soil	No data available.
12.5. Results of PBT and vPvB assessment	No data available.
12.6. Other adverse effects	No data available.

Section 13. Disposal Considerations.

13.1. Waste treatment methods

Disposal must be in accordance with local authority regulations.

Section 14. Transport Information.

Product identified in 1.1 with description stated in 1.2 is not classified as hazardous for transport.

Section 15. Regulatory Information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture No data available.

15.2. Chemical safety assessment No data available.

Section 16. Additional Information.

Full text of Statements used in Section 3;

H315 Causes skin irritation.

H350 May cause cancer.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

The above information is believed to be accurate and represents the best information currently available.

No warranty is expressed or implied by the above information.

We assume no liability resulting from use of the above information.

The end user should conduct their own investigations to determine the suitability of the above information for their particular purpose.

Issue level	Date	Revisions
1	24/11/2025	First issue.

End of Safety Data Sheet.