

VARIJIG FRAME SYSTEM

Adjustable frame and guide for use with a router.

- Adjustable frame for rectangles and squares.
- Allows a router to cut recesses, slots, face panel moulds etc.
- Four lengths of 27-1/2" extrusion with dual metric/imperial measuring scales.
- Working area 23-1/2" x 23-1/2".
- Cross cut accuracy to 5 thou. A square is required to square frame before use.
- Use with a guide bush with minimum 5/16" spigot length, or use Unibase as guide.
- Can also be used to create panel doors for kitchens etc.




Compatibility
www.trend-usa.com/compatibility

Includes:


- 4 x Alloy Extrusions with Scales
- 4 x Corner Brackets
- 1 x Anti-tilt Shoe
- 1 x Anti-tilt Shoe Fixing Screw




Product Reference:
U*VARIJIG



Rectangles




Squares



Anti-tilt Shoe

Replacement Parts:

- Frame Jointing Kit**
Set of four corner jointing brackets.
- U*VJS/FJK**



VARIJIG TENON & GROOVING JIG

Allows grooves & tenons to be cut using a router.

- Can be used to crosscut boards with router or circular saw.
- Frame is adjustable to allow narrower or wider grooves to be routed. The max. adjustment is 2-3/4" depending on the diameter of the router base.
- The edge of the frame can be used as a guide to trim a panel square using a router.
- Two sliding stops to set groove length.
- Squaring butt has the facility to accept a spelch block to allow a full-length groove. Fixing screws are included for this purpose.
- Working length is 15-3/4".
- Use with a router with a guide bush with a minimum 3/8" projection fitted.
- Requires two clamps.

Product Reference:
U*VJS/TG/JIG



Trimming



Crosscutting



Trenching/Grooving

Compatibility
www.trend-usa.com/compatibility

Router and clamps not included.

Includes:

- 4 x Alloy Extrusions
- 4 x Corner Brackets
- 3 x Scales
- 1 x Squaring Butt
- 2 x Length Stops
- 1 x Hex Key



Optional Accessories:

- F Clamp**
- U*FC/200** (1 off)
- Recommended 1-3/16" Guide Bush**
Euro Style with extra long 3/8" spigot.
- U*GB30/A**
- U*GB/US/30**

