
BEARING GUIDED TRIMMER

- Blades of cutters Refs. 46/01 & 46/03 can be rotated through 180° to give one new cutting
- Blades for Ref. 46/010 can be rotated by exchanging blades over.
- Ref. 46/02 has blades that can be rotated in 90° increments giving three extra new edges.







A Deg.	D mm	C mm	B mm	Product Ref.	Sh 1/4"	nank Diameter 1/2"
90°	12.7	8.0	12.7	46/01	£43.15	-
90°	12.7	20.0	12.7	46/010	£41.02	-
90°	19.0	12.0	19.0	46/02	£71.60	-
90°	19.0	30.0	19.0	46/03	£82.70	£82.70



'V' GROOVER **ENGRAVER**

- · Single blade.
- Blades can be rotated in 90° increments, giving three new edges.
- Ref. RT/80 is specifically designed for CNC machines.



Ref. RT/80 sign engraving in a ČNC machine.







	OL
A C	

Α	D	С	OL	Product	Shank I	Diameter
Deg.	mm	mm	mm	Ref.	1/4"	1/2"
45°	17.0	8.0	49.5	RT/81	£58.35	-
45°	17.0	8.0	60.0	RT/80	-	£72.24

STAIR HOUSING

- Designed for stair housing router machines and jigs. Please state LH or RH when ordering.
- Ref. RT/323 RH can be used for 32mm tread thickness in conjunction with Trend Stair Jig Ref. STAIR/A.
- Not for use on Pickles stair trenching machine.





	1 oL	
[9]	С	-
<u> </u>	╣┰┸	

A Deg.	D mm	C mm	OL mm	Product Ref.	Rotation	Shank Dia.	
95°	22.0	28.0	80.0	RT/323	LH	£106.27 +	

BEARING GUIDED REBATER Two blades. Ideal for rebating straight and shaped workpieces. • Low profile bearing fixing screw. D С E В Product Shank Dia. mm mm mm Ref.

13.25

9.5

9.5

28.6

DOUBLE BEARING GUIDED REBATER

- Fitted with two blades that can be rotated giving three new edges.
- Fitted with a double bearing.
- Bearing ring accessories can be fitted to give different rebate sizes. Rings are secured between the two bearings.



RT/391 £44.00 +

